



Model: SC2F-48

**DATA SHEET** 



## **POWER**

Motor: 48 Volt Toyota® AC 4kW

Battery: Lead Acid or LiT® Advanced Lithium Iron Phosphate

Charger: On Board - Delta Q

Transaxle: 10.25:1 High Speed Rear Axle

Controller: Toyota® 350 Amp.

## **PERFORMANCE**

Loading: Two Persons

Forward Speed: Up to 28 M.P.H.

Braking Distance: Approximately 7 Feet
Turning Radius: Approximately 10 Feet
Climbing: Safe Climb 25% / Max Climb 35%

Approx. Miles Per Charge: Lead 60 Miles / Lithium 120 Miles

## **STRUCTURE**

Chassis: A-Frame Powder Coated Steel. Four Wheel Coil Over

Shock.

Top Supports: Galvanized Steel. Anti Corrosive Dip With

Powder Coat. **Body**: PP Material

**Cart Dimensions**: 8 x 4 x 6 Feet **Ground Clearance**: 4.5 Inches

Net Weight: 595 Lbs.

## **EQUIPMENT**

Wheels: 8 Inch Aluminum

Other: Charge Indicator, Horn, Side Mirrors

Optional: SmartCart® Offers A Full Line Of Parts And Accessory

Upgrades







800-215-0253 www.SmartCartEV.com